



## SPARTA ADHESIVE APPROVED INSTALLATION TOOLS

	PRODUCT	TOOL	FLOORING TYPE	COVERAGE
WOOD	Honor MS <sup>95</sup>	BOND ONLY 1/8" x 1/8" x 1/8" Sq Notch	WOOD: Cork (flooring, cork-backed hardsurface, underlayment), Hardwood (parquet)	60-70 ft <sup>2</sup> /gal
		BOND ONLY 3/16" x 1/4" x 5/16" V Notch	WOOD: Acrylic Infused Plank, Bamboo, Hardwood (engineered, solid) RESILIENT: Rubber (crumb) Behind Hardwood (engineered, solid) Up to 1/2" thick	Up to 50 ft <sup>2</sup> /gal
		BOND ONLY 3/16" x 3/16" x 3/16" Sq Notch	WOOD: Hardwood (engineered, solid) 1/2" up to 9/16" thick	Up to 30 ft <sup>2</sup> /gal
		MOISTURE BARRIER & SOUND CONTROL 1/4" x 1/4" V Notch	WOOD: Acrylic Infused Plank, Bamboo, Hardwood (engineered, solid [planks less than 6' long and 5" wide])	25-30 ft <sup>2</sup> /gal
		MOISTURE BARRIER & SOUND CONTROL 1/2" x 15/32" V Notch	WOOD: Acrylic Infused Plank, Bamboo, Hardwood (engineered, solid [planks greater than 6' long and 5" wide])	Up to 20 ft <sup>2</sup> /gal
	Hoplite UR <sup>75</sup>	BOND ONLY 1/16" x 1/16" x 1/16" Sq Notch	WOOD: Cork (underlayment), RESILIENT: Rubber (crumb)	150-180 ft <sup>2</sup> /gal
		BOND ONLY 1/8" x 1/8" x 1/8" Sq Notch	WOOD: Cork (flooring, underlayment), Hardwood (parquet) RESILIENT: Rubber (crumb)	60-70 ft <sup>2</sup> /gal
		BOND ONLY 3/16" x 1/4" x 5/16" V Notch	WOOD: Acrylic Infused Plank, Bamboo (not strand woven), Cork (flooring, cork-backed hard surface, underlayment), Hardwood (engineered, parquet, solid)	Up to 50 ft <sup>2</sup> /gal
BOND ONLY 3/16" x 3/16" x 3/16" Sq Notch		WOOD: Hardwood (engineered, solid) 1/2" up to 9/16" thick	Up to 30 ft <sup>2</sup> /gal	
PRESSURE SENSITIVE	Warloc PS	BOND ONLY 1/16" x 1/32" x 1/32" U Notch	RESILIENT: Modular (LVP/LVT [non-porous], SVT, VCT, VET), Sheet (heterogeneous/homogeneous [non-porous]) Stair Treads (rubber/vinyl [non-porous]) CARPET: Modular (hard-backed/soft-backed [non-porous])	220-260 ft <sup>2</sup> /gal
		BOND ONLY 1/16" x 1/16" x 1/16" Sq Notch	RESILIENT: Linoleum, Modular (LVP/LVT [porous], rigid core [dryback]) Rubber (crumb, sheet, tile), Sheet (heterogeneous/homogeneous [porous]), Stair Treads (rubber/vinyl [porous]) CARPET: Broadloom (6 ft vinyl-backed, double-stick-cushion-to-substrate) Modular (hard-backed/soft-backed [porous], walk-off) WOOD: Cork (cork-backed hard surface, underlayment)	150-180 ft <sup>2</sup> /gal
		BOND ONLY 1/8" x 1/8" x 1/16" V Notch	CARPET: Broadloom (Action-Bac, jute-back, hot-melt-backed, HP & vinyl-backed, polyurethane, rubber-backed, unitary Action-Bac)	90-120 ft <sup>2</sup> /gal
		BOND ONLY 1/8" x 1/8" 1/16" U Notch	CARPET: Broadloom (double-stick carpet-to-cushion, unitary, woven-backed)	50-65 ft <sup>2</sup> /gal
		BOND ONLY 3/8" Short Nap Paint Roller	RESILIENT: Sheet (fiberglass) CARPET: Modular (hard-backed)	Up to 350 ft <sup>2</sup> /gal
PRIMER	Phalanx PR	PRIMER ONLY 3/8" Short Nap Paint Roller	For use under all glue-down, loose-lay, and floating floors	300-450 ft <sup>2</sup> /gal

## SPARTA ADHESIVE PACKAGING & SHIPPING

	PRODUCT	SIZE	PACKAGING	UPC (SKU)	#/ UNIT	UNIT WEIGHT*	UNITS/PALLET	SHelf LIFE
WOOD	Honor MS <sup>95</sup>	4 gal	Plastic Pail	4403_0323	1	43 lbs	48	1 year
	Hoplite UR <sup>75</sup>	4 gal	Metal Pail	4402_0323	1	57 lbs	48	1 year
PRESSURE SENSITIVE	Warloc PS	4 gal	Plastic Pail	4401_0323	1	37 lbs	48	2 years
PRIMER	Phalanx PR	4 gal	Plastic Pail	4404_0323	1	37 lbs	48	2 years

### STORAGE REQUIREMENTS

All SPARTA Adhesive products should be stored in their original container, unopened, at temperatures between 50-90°F (10-32° C). While most products are freeze-thaw stable (10°F [-12°C]), it is necessary to protect them from freezing. Some products must be protected from freezing. See each product's technical data sheet (TDS) for complete details.





## SPARTA ADHESIVE APPROVED FLOORING TYPES

FLOORING TYPE		HONOR MS <sup>95</sup>	HOPLITE UR <sup>75</sup>	WARLOC PS
RESILIENT	LINOLEUM			✓
	MODULAR (LVP, LVT)			✓
	MODULAR (RIGID CORE - DRYBACK)			✓
	MODULAR (SVT, VET)			✓
	MODULAR (VCT)			✓
	RUBBER (CRUMB)	✓	✓	✓
	RUBBER (SHEET & TILE)			✓
	SHEET (FIBERGLASS)			✓
	SHEET (HETEROGENEOUS)			✓
	SHEET (HOMOGENEOUS)			✓
	STAIR TREADS (RUBBER, VINYL)			✓
	WOOD	ACRYLIC INFUSED PLANK	✓	✓
BAMBOO (STRAND WOVEN)		✓		
BAMBOO (NOT STRAND WOVEN)		✓	✓	
CORK (FLOORING)		✓	✓	
CORK (CORK-BACKED HARD SURFACE)		✓	✓	✓
CORK (UNDERLAYMENT)		✓	✓	✓
HARDWOOD (ENGINEERED, PARQUET)		✓	✓	
HARDWOOD (SOLID)		✓	✓	
CARPET	BROADLOOM (6-FT VINYL-BACKED)			✓
	BROADLOOM (ACTION-BAC, JUTE-BACK)			✓
	BROADLOOM (DOUBLE STICK - CARPET TO CUSHION)			✓
	BROADLOOM (DOUBLE STICK - CUSHION TO SUBSTRATE)			✓
	BROADLOOM (HOT-MELTED-BACKED)			✓
	BROADLOOM (HP & VINYL-BACKED)			✓
	BROADLOOM (NON-VINYL-BACKED PATTERNED)			✓
	BROADLOOM (POLYURETHANE, RUBBER-BACKED)			✓
	BROADLOOM (UNITARY & UNITARY ACTION-BAC)			✓
	BROADLOOM (WOVEN-BACKED)			✓
	MODULAR (HARD-BACKED CARPET TILE)			✓
	MODULAR (SOFT-BACKED CARPET TILE)			✓
	MODULAR (WALK-OFF CARPET TILE)			✓

**NOTE:** Phalanx PR primer is not restricted by flooring types, so it does not appear in the chart above.

