



FIRM-SET, MODIFIED  
ADAPTIVE PRESSURE  
SENSITIVE ADHESIVE



**WARLOC PS**

## WARRANTY CERTIFICATE

LW Flooring provides a 10-year limited adhesive bond warranty when *Warloc PS* is used for the interior installation of approved flooring products over properly prepared substrates (see current technical data sheet for complete details).

*Warloc PS* shall be free from manufacturing defects and will perform as designed when properly used.

Substrates shall be properly prepared per ASTM F710, have an intact moisture vapor retarder per ASTM E1745, and be without hydrostatic pressure. The installation must be performed following both LW Flooring's guidelines for flooring and adhesives. For the latest product information and application instructions please visit [www.lwflooring.com](http://www.lwflooring.com).

If an installation failure occurs as a direct result of the use of defective *Warloc PS*, LW Flooring will pay for equivalent floor covering, replacement *Warloc PS*, and for reasonable labor costs to repair or replace the failed portion of the installation as determined by LW Flooring at its sole discretion. This warranty applies only to *Warloc PS* related bond failures. LW Flooring cannot warrant those variables over which it has no control such as the quantity of *Warloc PS* used, the workmanship of the installer, the condition of the subfloor, excessive moisture, excessive pH, the stability of the flooring product and its suitability for installation on the affected job-site, or any other conditions that might affect the installation.

LW Flooring reserves the right as deemed necessary to inspect any claim for cause or this warranty is null and void. Any repairs done prior to inspection by a LW Flooring representative voids any warranty. This warranty is non-transferable.

**Order Now**  
(352) 328-7491



[www.lwflooring.com](http://www.lwflooring.com)



[info@lwflooring.com](mailto:info@lwflooring.com)



(352) 328-7491